

Motorcycle – Air Filter Product

Version: EC2/001

Valvoline™ Air Filter Oil

A special motorcycle oil for foam-plastic air filters, specifically developed to prevent dirt and debris entering the motorcycle engine.

Air Filter Oil is highly adhesive and sticks to the foam air filter, blocking any dust, dirt, sand and grime particle that tries to enter the carburettor or the engine combustion chamber.

Applications

Suitable to protect virtually all motorcycle engines and other foam rubber air filters

Air Filter Oil prevents dust, dirt, sand and grime entering the motorcycle engine.

Easy to use:

Shake well before use. Dip the air filter in the oil and rinse it well with the product. Slowly squeeze the air filter in order to drain the surplus of the oil. Do not wring the air filter! Put the filter on paper or on an old cloth and let it dry for 20 minutes.

Features & Benefits

Excellent protection and penetration ability

Air Filter Oil is highly adhesive and sticks to the foam air filter, blocking any dust, dirt, sand and grime particle that tries to enter the carburetor or the engine combustion chamber.

Excellent performance and longer engine life

The composition of the product contains specially selected base oils, solvents, and several additives, that give the product excellent properties, like; high adhesion, maximum penetration ability, high resistance against oxidation and ageing

Excellent removal of dust and sand from the intake air. A cleaner air intake means a cleaner engine and longer engine life.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Air Filter Oil	
Colour	Blue
Boiling Point, °C	65-70
Specific Gravity @ 15.6°C. ASTM D-4052	0,785
Flash Point, COC, °C. ASTM D-92	Flammable liquid

This information only applies to products manufactured in the following location(s): Europe

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –

™ Trademark of Valvoline, registered in various countries © 2019

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.